

## Finished Product Details

Application	Soccer/AFL
Pile Height (mm)	40mm
Colours Available	Field Green
Total Product Weight g/m <sup>2</sup>	2,578 g/m <sup>2</sup>

## Supply

Available Width	3.71m
Standard Roll Length	As required (max. 55LM)
Approx. Shipping Weight	9.6 kg/lm
Line Systems	Tufted as required

## Infill Materials

Stabilising Infill	Washed and Dried Fine Silica Sand (10kg/m <sup>2</sup> )
Performance Infill	Black SBR 0.7mm - 2.0mm (10kg/m <sup>2</sup> )

## Product Warranty

Warranty	Eight (8) year limited warranty as per manufacturer's standard warranty terms
----------	---

## Configuration

Machine Gauge	9.52mm (3/8")
Stitch Rate	12 per 100mm
Yarn Weight	1,338 g/m <sup>2</sup>
No. of Tufts (m <sup>2</sup> )	12,598
Perforated	Yes

## Yarn Properties

Yarn Construction	PE Ultimate M & PE Ultimate HP
Linear Density	1,200 Tex
Environment	APTA(manufacturer) manufacturers with heavy metal free yarns which may be used anywhere without restriction
UV Stability	APTA yarns are protected against UV degradation and light fastness meets the highest standards

## Primary Backing

Construction	UV resistant, non fibrillated plain polypropylene fabric
Primary Layers	Double

## Secondary Coating

Compound Base	Hybrid Emulsion
Tuft Anchorage	40 Newtons (minimum)
Antioxidising Agent	Present

## Shockpad

Composition	Proplay Pads 23
Thickness (mm)	23mm